



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
ANM04.001.01.028AB	UL1617	600V	1X28AWG	11/0.1	2.2	6.59	223 Ω/km
ANM04.001.01.027AB	UL1617	600V	1X27AWG	7/0.14	2.3	7.21	175 Ω/km
ANM04.001.01.026AB	UL1617	600V	1X26AWG	9/0.14	2.3	7.53	140 Ω/km
ANM04.001.01.025AB	UL1617	600V	1X25AWG	11/0.14	2.4	8.27	111 Ω/km
ANM04.001.01.024AB	UL1617	600V	1X24AWG	14/0.14	2.4	8.71	87.6 Ω/km
ANM04.001.01.023AB	UL1617	600V	1X23AWG	17/0.14	2.5	9.66	69.2 Ω/km
ANM04.001.01.022AB	UL1617	600V	1X22AWG	22/0.14	2.6	10.73	55.4 Ω/km
ANM04.001.01.021AB	UL1617	600V	1X21AWG	27/0.14	2.7	12.12	43.6 Ω/km
ANM04.001.01.020AB	UL1617	600V	1X20AWG	34/0.14	2.8	13.62	34.6 Ω/km
ANM04.001.01.019AB	UL1617	600V	1X19AWG	43/0.14	2.9	15.46	27.4 Ω/km
ANM04.001.01.018AB	UL1617	600V	1X18AWG	29/0.19	3	17.73	21.8 Ω/km
ANM04.001.01.017AB	UL1617	600V	1X17AWG	37/0.19	3.2	20.84	17.3 Ω/km
ANM04.001.01.016AB	UL1617	600V	1X16AWG	27/0.25	3.5	25.71	13.7 Ω/km
ANM04.001.01.015AB	UL1617	600V	1X15AWG	34/0.25	3.7	30.15	10.9 Ω/km
ANM04.001.01.014AB	UL1617	600V	1X14AWG	43/0.25	3.9	35.58	8.62 Ω/km
ANM04.001.01.013AB	UL1617	600V	1X13AWG	54/0.25	4.2	42.73	6.82 Ω/km
ANM04.001.01.012AB	UL1617	600V	1X12AWG	68/0.25	4.6	53.01	5.43 Ω/km
ANM04.001.01.011AB	UL1617	600V	1X11AWG	85/0.25	5	63.97	4.30 Ω/km
ANM04.001.01.010AB	UL1617	600V	1X10AWG	108/0.25	6.2	86.87	3.409 Ω/km
ANM04.001.01.009AB	UL1617	600V	1X9AWG	136/0.25	6.9	109.54	2.705 Ω/km
ANM04.001.01.008AB	UL1617	600V	1X8AWG	171/0.25	7.3	130.67	2.144 Ω/km
ANM04.001.01.007AB	UL1617	600V	1X7AWG	84/0.4	7.7	156.45	1.700 Ω/km
ANM04.001.01.006AB	UL1617	600V	1X6AWG	106/0.4	8.4	190.5	1.348 Ω/km
ANM04.001.01.005AB	UL1617	600V	1X5AWG	134/0.4	9	231.27	1.070 Ω/km
ANM04.001.01.004AB	UL1617	600V	1X4AWG	169/0.4	10.3	296.55	0.8481 Ω/km
ANM04.001.01.003AB	UL1617	600V	1X3AWG	213/0.4	11.1	361.27	0.6727 Ω/km
ANM04.001.01.002AB	UL1617	600V	1X2AWG	268/0.4	12.8	465.32	0.5335 Ω/km
ANM04.001.01.001AB	UL1617	600V	1X1AWG	338/0.4	14.1	580.01	0.4230 Ω/km
ANM04.001.01.1/0AB	UL1617	600V	1X1/0AWG	426/0.4	15.4	711.09	0.3354 Ω/km
ANM04.001.01.2/0AB	UL1617	600V	1X2/0AWG	537/0.4	16.7	871.93	0.2660 Ω/km
ANM04.001.01.3/0AB	UL1617	600V	1X3/0AWG	677/0.4	18.8	1105.51	0.2110 Ω/km
ANM04.001.01.4/0AB	UL1617	600V	1X4/0AWG	854/0.4	20.4	1359.2	0.1673 Ω/km
ANM04.001.01.250kB	UL1617	600V	1X250Kcmil	1007/0.4	22.5	1617.9	0.1416 Ω/km
ANM04.001.01.300kB	UL1617	600V	1X300Kcmil	1184/0.4	23.6	1895.4	0.1180 Ω/km
ANM04.001.01.350kB	UL1617	600V	1X350Kcmil	1406/0.4	25.1	2179	0.1011 Ω/km
ANM04.001.01.400kB	UL1617	600V	1X400Kcmil	1628/0.4	26.6	2473.1	0.08851 Ω/km
ANM04.001.01.450kB	UL1617	600V	1X450Kcmil	1830/0.4	27.8	2752	0.07867 Ω/km
ANM04.001.01.500kB	UL1617	600V	1X500Kcmil	2013/0.4	28.8	3028.1	0.07080 Ω/km